



### Vented Safety Lid

Stops operation when the lid is removed. Creates air flow to minimize gel warping due to overheating.

### Integrated Timer

With a setting from 1 to 99 minutes, automatic shut-off, or indefinite hold regime.

### Convenient Voltage Presets

Membrane keyboard with 3 voltage presets of 35V, 50V, and 100V lets you start your gel run faster.



### Compact Design

Only 7.5" x 5" footprint (including gel tank and power supply)

### Simple Gel Casting

All accessories included.  
No spacer or clamps needed.  
Can cast multiple gels in parallel.

### Integrated Power Supply

No external power supply is needed, saving you valuable bench space and money.



## PuroGEL™ Compact Gel Electrophoresis System

**Compact • Affordable • Easy-to-use • Complete System**

Compact agarose gel electrophoresis system with integrated power supply.

## PuroGEL™ Compact Gel Electrophoresis System

### Features

- Complete system - gel tank, integrated power supply, gel casting accessories
- Compact design - 7.5" x 5" footprint (including gel tank and power supply)
- Quick and simple gel casting - no spacers or clamps needed, all accessories included
- Membrane keypad with 3 voltage presets (35V, 50V, 100V) and a timer with 1 to 99 minute setting
- Vented safety lid prevents operation when the cover is open and dissipates heat during the run
- Integrated power supply - no external power supply required

### Package Content

- Gel system (gel migration tank, safety lid, control box with integrated power supply)
- Two 10.5 x 6 cm gel trays, four 5 x 6 cm gel trays
- Two casting stands
- Two 22/12 tooth and two 18/12 tooth double sided combs (compatible with multichannel pipette)

### Ordering Information

Product Code	Product Description	Price
<b>PG-ES03</b>	PuroGEL™ Compact Gel Electrophoresis System	<b>\$387.60</b>

### Specifications

Parameter	Value
Output Voltage	35V, 50V, 100V
Timer	1-99 minutes / continuous
Dimensions	7.5 x 5.1 x 2.1 in (19 x 13 x 5.5 cm)
Gel Capacity	One 10.5 x 6 cm / Two 5 x 6 cm
Maximum Tank Volume	230 mL
Safety	Magnetic / mechanical lid interlock
Weight	1 lb / 0.45 kg
Electrical Input	115V, 50-60Hz