GREENFIELD

SAFETY DATA SHEET

1. Identification

Product identifier Ethyl alcohol, anhydrous

Other means of identification

CAS number 64-17-5

Synonyms Ethanol, Absolute ethanol, Alcohol (anhydrous), Ethyl alcohol 200 proof

Recommended useGeneral purpose solvent.

Recommended restrictionsRefer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

Company name Greenfield Global Inc. **Address** 6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

Telephone (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CANUTEC: (613) 996-6666

2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire:

Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Ethyl alcohol		64-17-5	100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Ethyl alcohol, anhydrous SDS Canada

956948 Version #: 01 Revision date: - Issue date: 01-February-2021

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eve contact

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods General fire hazards Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Ethyl alcohol, anhydrous SDS Canada

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occu	national	exposure	limits
Occu	pational	CAPOSUIC	11111113

Thermal hazards

US. ACGIH Threshold Limit Material	Type	Value	
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
Canada. Alberta OELs (Occi Material	upational Health & Safety Code, Scho Type	edule 1, Table 2) Value	
Ethyl alcohol (CAS 64-17-5)	TWA	1880 mg/m3	
		1000 ppm	
Canada. British Columbia O Safety Regulation 296/97, as		for Chemical Substances, Occupational Health and	
Material	Туре	Value	
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
Canada. Manitoba OELs (Re	g. 217/2006, The Workplace Safety A	and Health Act)	
Material	Туре	Value	
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
Canada. Ontario OELs. (Cor Material	ntrol of Exposure to Biological or Che	emical Agents) Value	
	Type		
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
Canada. Quebec OELs. (Min Material	istry of Labor - Regulation respectin Type	g occupational health and safety) Value	
Ethyl alcohol (CAS 64-17-5)	TWA	1880 mg/m3	
		1000 ppm	
Canada. Saskatchewan OEL Material	s (Occupational Health and Safety R. Type	egulations, 1996, Table 21) Value	
Ethyl alcohol (CAS 64-17-5)	15 minute	1250 ppm	
	8 hour	1000 ppm	
logical limit values	No biological exposure limits noted for	or the ingredient(s).	
oropriate engineering atrols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
ividual protection measures,	such as personal protective equipm	ent	
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Butyl rubber or Viton® gloves are recommended. Other suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.		
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure		

Ethyl alcohol, anhydrous SDS Canada

Wear appropriate thermal protective clothing, when necessary.

organic vapour cartridge and full facepiece.

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with

956948 Version #: 01 Revision date: -Issue date: 01-February-2021 General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Colour Clear liquid; invisible vapour.

Odour Sweet. Alcohol-like.

Odour threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling 78.33 °C (173 °F)

range

Flash point 12.8 °C (55.0 °F) Closed cup

Evaporation rate May evaporate quickly.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

3.3 %

(%)

Flammability limit - upper

19 %

(%)

Vapour pressure 59.5 hPa (20 °C (68 °F))

Vapour density 1.6

Relative density 0.785 g/ml (25 °C (77 °F))

Solubility(ies)

Solubility (water) Completely soluble.

Partition coefficient

Not available

(n-octanol/water)

Auto-ignition temperature 363 °C (685.4 °F)

Decomposition temperature Not pertinent

Viscosity Not available.

Other information

Explosive properties

Molecular formula

C2-H6-O

Molecular weight

Oxidising properties

Not explosive.

A6.07 g/mol

Not oxidising.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Causes serious eye irritation.

Ethyl alcohol, anhydrous SDS Canada

956948 Version #: 01 Revision date: - Issue date: 01-February-2021

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity

Product Species Test Results

Ethyl alcohol (CAS 64-17-5)

Acute Inhalation

Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Prolonged skin contact may cause temporary irritation.

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Canada - Manitoba OELs: carcinogenicity

Ethyl alcohol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity Possible reproductive hazard.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
Ethyl alcohol (CAS 64-	17-5)			
Aquatic				
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours	
	EC50	Freshwater algae	275 mg/l, 72 hours	
		Marine water algae	1900 mg/l	
	NOEC	Marine water algae	1580 mg/l	
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours	
	NOEC	Freshwater fish	250 mg/l	
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours	
		Marine water invertebrate	857 mg/l, 48 hours	
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days	
		Marine water invertebrate	79 mg/l, 96 hours	
Other	EC50	Lemna minor	4432 mg/l, 7 days	
	NOEC	Lemna minor	280 mg/l, 7 days	

Ethyl alcohol, anhydrous SDS Canada

956948 Version #: 01 Revision date: - Issue date: 01-February-2021

Product Species Test Results

Other

Micro-organisms LC50 Micro-organisms 5800 mg/l, 4 hours

Terrestrial

Plant EC50 Terrestrial plant 633 mg/kg dw

Persistence and degradabilityExpected to be readily biodegradable.Bioaccumulative potentialPotential to bioaccumulate is low.Mobility in soilExpected to be highly mobile in soil.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN1170 UN proper shipping name ETHANOL

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1170 UN proper shipping name Ethanol

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II
Environmental hazards No
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1170 UN proper shipping name ETHANOL

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group ||

Environmental hazards

Marine pollutant No EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

This product is a liquid and when transported in bulk is covered under MARPOL 73/78 Annex II.

This product is listed in the IBC Code.

the IBC Code Pollution category: Z

Ethyl alcohol, anhydrous SDS Canada

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information

Issue date 01-February-2021

Revision date - 01

Disclaimer This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at

http://www.greenfield.com/tc-po-can/. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the

time of writing.

Ethyl alcohol, anhydrous SDS Canada

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).